

We claim:

1. A barrier device for obstructing entry travel routes into enclosed and semi-enclosed spaces, comprising:

5 a barrier material sized to fit adjacent to an attachment portion between a fixture and a fixed-permanent surface in a room, the barrier material substantially closing off a passageway along where crawling arthropods can enter the room; and

an arthropod repellant substance associated with the barrier material for deterring the crawling arthropods from entering into the room along the passageway.

10

2. The barrier device of claim 1, wherein the fixed-permanent surface is selected from a surface portion of at least one of: a wall, a ceiling, and a floor.

15

3. The barrier device of claim 2, wherein the fixed-permanent surface includes: a wall portion.

4. The barrier device of claim 2, wherein the fixed-permanent surface includes: a floor portion.

20

5. The barrier device of claim 2, wherein the fixed permanent surface includes: a ceiling portion.

6. The barrier device of claim 2, wherein the fixture includes: an attachment point between shower faucet handles and the surface portion.

25

7. The barrier device of claim 6, wherein the barrier material includes: a disc shape with a center through-hole therethrough for fitting adjacent to the attachment point between the shower faucet handles and the surface portion.

5 8. The barrier device of claim 2, wherein the fixture includes: an attachment point between a pipe and the surface portion.

9. The barrier device of claim 8, wherein the barrier material includes: a conical shape with a center through-hole therethrough for fitting adjacent to the attachment point between
10 the pipe and the surface portion.

10. The barrier device of claim 9, wherein the center through-hole further includes:
a variable size opening for fitting about different pipe diameters.

15 11. The barrier device of claim 8, wherein the pipe includes: a drainline for a sink.

12. The barrier device of claim 8, wherein the pipe includes: an incoming waterline for a sink.

20 13. The barrier device of claim 8, wherein the pipe includes: a water line for a showerhead.

14. The barrier device of claim 2, wherein the fixture includes: a stem extending into the room, the stem between the surface portion and an electric powered fixture.

25

15. The barrier device of claim 14, wherein the electric powered fixture includes: a ceiling fan.

16. The barrier device of claim 14, wherein the electrical powered fixture includes: a light.

5 17. The barrier device of claim 14, wherein the barrier material includes:
a bell shape with a center through-hole therethrough for fitting about the stem.

18. The barrier device of claim 17, wherein the center through-hole further includes:
a variable size opening for fitting about different stem diameters.

10

19. The barrier device of claim 2, wherein the fixture includes: a drain receptical.

20. The barrier device of claim 19, wherein the barrier material includes:
a cup shaped insert having a center through-hole for fitting with the drain

15 receptical.

21. The barrier device of claim 2, wherein the fixture includes: an air vent cover.

22. The barrier device of claim 21, wherein the barrier material includes:

20 a rectangular shaped insert having a rectangular shaped opening for fitting with the
vent cover.

23. The barrier device of claim 2, wherein the fixture includes: a wall switch and a
cover.

25

24. The barrier device of claim 23, wherein the barrier material includes:

a rectangular shaped insert having at least one through-hole for a toggle switch for fitting between the cover and the wall switch.

5 25. The barrier device of claim 2, wherein the fixture includes: telephone jack and a cover.

26. The barrier device of claim 25, wherein the barrier material includes:
a rectangular shaped insert having at least one through-hole for a telephone jack connector for fitting between the cover and the telephone jack.

10

27. The barrier device of claim 2, wherein the fixture includes: a thermostat mounted to a wall portion.

15

28. The barrier device of claim 27, wherein the barrier material includes:
a rectangular shaped insert having a through-hole therethrough for fitting between the thermostat and the wall portion.

29. The barrier device of claim 2, wherein the fixture includes: an electrical socket and a cover.

20

30. The barrier device of claim 29, wherein the barrier material includes:
a rectangular shaped insert having at least one through-hole therethrough for fitting between the electrical socket and the cover.

25 31. The barrier device of claim 2, wherein the fixture includes: a cable socket and a cover.

32. The barrier device of claim 31, wherein the barrier material includes:
a rectangular shaped insert having at least one through-hole therethrough for fitting
between the cable socket and the cover.

5 33. The barrier device of claim 1, further comprising: a package for housing at least
one barrier material.

34. A method for impeding a route of travel for crawling arthropods from entering
along surface attached fixtures in enclosed and semi-enclosed spaces, comprising the steps
10 of:
associating an arthropod deterring substance with a barrier material; and
positioning the barrier material about a surface attachment portion for a fixture
within an interior space, wherein the barrier material impedes the arthropods from traveling
into the space.

15 35. The method of claim 34, wherein the positioning step includes:
positioning the barrier material adjacent a wall surface attachment portion.

36. The method of claim 34, wherein the positioning step includes:
20 positioning the barrier material adjacent a ceiling surface attachment portion.

37. The method of claim 34, wherein the positioning step includes:
positioning the barrier material adjacent a floor surface attachment portion.